



Specification

| | |
|------------------|--|
| Graphic display | Q - 5,7" TFT LCD, 320 x 240 pixel, 262 k colours or |
| Input | Touchscreen resistiv |
| Audio | Beeper |
| Processor | 32 Bit Cortex-A8 RISC CPU 600 MHz |
| Memory | 256 MB RAM, 512 MB Flash, 1 MB NVRAM |
| Memory expansion | SD Card, SDHC Card bis 32 GB* |
| Data buffering | Persistent data in flash, real-time clock and retain data battery-buffered |

Software

| | |
|---------------------------|---|
| Operating system | Microsoft Windows Embedded Compact 7 |
| PLC programming | IEC 61131-3, CODESYS V3.x |
| HMI programming | TargetVisu |
| C, C++ and C# programming | Microsoft Visual Studio 2005/2008 (Visual C++) with SDK |

Interface

| | |
|---------------------|--|
| Ethernet | 1 x 10/100 BASE-T, RJ45 |
| Field bus interface | 1 x CAN acc. ISO 11898 with galvanic isolation, RJ45 |
| Serial interface | 1 x RS-232 with galvanic isolation, D-Sub-9 plug |
| USB | 2 x 2.0 Host, type A |

Order-No.:

24792.7001 PMC405Q/CS3/TV/elrest/L

| Environment/mechanical values | |
|--|--|
| Supply voltage | 24 V DC (18 V...30 V), 8 W...12 W |
| Housing | Plastic |
| EMC examinations | EN 61000-6-2, EN 61000-6-4 |
| Environment audit | EN 60068-2-6, EN 60068-2-27 |
| IP Rating | Front IP54, Back IP20 acc. EN 60529 |
| Mounting | With terminal blocks |
| Outside dimension in mm (W x H x D) | 208 x 150 x 50 |
| Cut-out dimension in mm (W x H) | 198 x 138 |
| Weight approx. | 800 g |
| Operating temperature | 0 °C...50 °C |
| Storage temperature | -20 °C...70 °C |
| Relative humidity for operation | 10%...85% no condensing |
| Air pressure (storage) | min. 660 hPa, corresponding to a height of max. 3500m |
| Air pressure (operation) | min. 795 hPa, corresponding to a height of max. 2000m |
| Concentration of pollutants (operation/storage) | SO ₂ : < 0,5 ppm; relative humidity < 60 %, no condensation H ₂ S: < 0,1 ppm; relative humidity < 60 %, no condensation |

Illustrations, descriptions, dimensions and specifications correspond to the circumstances or intentions at the time of printing this brochure. Changes of any kind, especially those resulting from technological progress, economic performance or a similar will be without notice. The external interconnection of equipment will be on your own responsibility

*Remark: The use of standard memory card (e.g. CF-cards) is generally possible. Anyhow elrest GmbH does not take any responsibility thereby.

elrest Automationssysteme GmbH • Leibnizstraße 10 • 73230 Kirchheim unter Teck • Tel.: +49 (0) 7021 92025-0

© 2015 • www.elrest.de • All rights reserved

E601146-1.0

