



• PCAP Touch • Control panel • Web configuration

Specification		
Graphic display		color TFT LCD 7,0" TFT, 1280 x 800 pixel, (16:9)
Input		PCAP touch screen (cover glass)
Memory		1GB DDR3 RAM; 4GB eMMC onboard
Processor		ultra low power Freescale ARM® Cortex™ A9 Dual Core 800 MHZ
Data buffering		RTC via Goldcap, 5 days buffering time
	optional	battery buffered
Software		
Operating system		Linux
Interface		
Ethernet		2 x 100/1000BASE-T, RJ45
Field bus interface		1 x CAN acc. ISO 11898 with galvanic isolation, RJ45
	optional	1 x CAN acc. ISO 11898 with galvanic isolation, D-Sub-9 plug
Serial interface		1 x RS-232 with galvanic isolation, D-Sub-9 plug
	optional	1 x RS-232 and RS-422/RS-485 with galvanic isolation, D-Sub-9 plug
USB		1 x 2.0 Host, type A
Audio	optional	Beeper, optional: Line IN, Line OUT
Order-No.:		
24AD1.xxxx		PTE510/L/2/P/elrest-ALL

Environment/mechanical values	
Supply voltage	24 V DC (18 V...30 V), 6 W...10 W
Power consumption (duration/start-up)	0,35A/0,56A
Housing	Metal housing, glass
IP Rating	Front IP54, Back IP20 acc. EN 60529
Mounting	Front panel mounting
Outer dimension in mm (W x H x D) approx.	286 x 208 x 36
Cutout in mm (W x H) approx.	270 x 192
Weight approx.	2050 g
Operating temperature	0 °C...45 °C
Storage temperature	-20 °C...70 °C
Relative humidity for operation	10%...85% non-condensing
Relative humidity for storage	5%...85% non-condensing
Standards	
Product standard	EN 61000-6-2:2015 EN 61000-6-3:2011
Accessory	
Mounting material	1 x MB225-4 terminal block set Number of the terminal blocks per device:8 pieces
Battery	1 x VARTA CR1/2 AA 3 V Lithium

© 2017 elrest Automationssysteme GmbH. All rights reserved.

The information contained in this document is subject to change without notice and do not constitute any obligation on the part of elrest Automationssysteme GmbH. The software and / or databases described in this document, are provided under a license agreement and a secrecy agreement. The software and / or databases may only be used or copied in accordance with the terms of the agreement. It is unlawful to copy the software to another medium, as far as this is not expressly permitted in the license or secrecy agreement. Without the express written permission of elrest Automationssysteme GmbH neither this manual nor parts thereof may be used for any purpose, in any form by any means, electronically or mechanically, reproduced or transmitted by photocopy or recording.

Illustrations and descriptions as well as dimensions and technical data correspond to the circumstances or intentions at the time of the printing of this brochure. We reserve the right to make changes of any kind, in particular as far as they result from technical progress, economic execution or similar. The external connection of the devices is carried out by the user.

Do you have questions, requests or suggestions?

You can in-depth comprehensive information about elrest on our website: www.elrest.de

Your direct line to elrest: +49 (0) 7021-92025-0

or contact us at: vertrieb@elrest.de



E601014-1.3

elrest Automationssysteme GmbH • Leibnizstraße 10 • D-73230 Kirchheim unter Teck
 Tel: +49 (0) 7021-92025-0 • Fax: +49 (0) 7021-92025-29 • vertrieb@elrest.de • www.elrest.de

Illustrations and descriptions as well as dimensions and technical data correspond to the circumstances or intentions at the time of this brochure. Changes of any kind, in particular as far as they result from technical progress, economic performance or shall remain reserved.

